

Head office :1728-1 OMAEDA FUKAYA-SHI,SAITAMA-KEN, 369-1295 JAPAN Battery Dept :3-12 SHIOHAMA, ICHIKAWA-SHI,CHIBA-KEN, 272-0127 JAPAN

Reference No. MHK 230202T

SAFETY DATA SHEET

The batteries are exempt articles and are not subject to the OSHA Hazard Communication Standard Requirement. This sheet is provided as technical information only. The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. However, Mitsubishi Electric Home Appliance Co.,Ltd. makes no warranty expressed or Implied.

1. Product and Company Identification

Product Name: Alkaline Button Cell	Effective Date From:
Size: LR44, LR41, LR1130, LR626	January 1, 2023
Company:	Telephone Numbers:
Mitsubishi Electric Home Appliance Co., Ltd.	81- (0)47-712-7500
Address (Number, Street, City, State, and ZIP Code):	Fax Numbers:
3-12,Shiohama, Ichikawa-shi,Chiba,272-0127 Japan	81- (0)47-307-6010

2. Composition/Information on Ingredients

Ingredient	CAS No.	Contents
Manganese dioxide [MnO ₂]	1313-13-9	< 30 wt%
Graphite [C]	7782-42-5	< 4 wt%
Zinc [Zn]	7440-66-6	< 12 wt%
Electrolyte [KOH solution]	1310-58-3	< 4 wt%
Lead [Pb]	7439-92-1	Additive-free
Mercury [Hg]	7439-97-6	Additive-free
Cadmium [Cd]	7440-43-9	Additive-free

3. Hazards Identification

Routes of Entry: Not applicable under normal conditions

Health Hazards: In case of leakage, will be cause itchy and/or chemical

burns when direct contact with electrolyte Hazards to Environment: Not applicable Fire and Explosion Hazards: Not applicable



Head office :1728-1 OMAEDA FUKAYA-SHI,SAITAMA-KEN, 369-1295 JAPAN Battery Dept :3-12 SHIOHAMA, ICHIKAWA-SHI,CHIBA-KEN, 272-0127 JAPAN

4. First-aid Measures

Skin Contact: If exposed to a leaking battery, remove contaminated clothing. Wash exposed areas with plenty of water and soap. If irritation occurs, consult a physician.

Eyes Contact: If a battery is leakage and materials contact eyes, flush immediately with running water for at least 15 minutes. Consult an ophthalmologist at once.

Inhalation: If vapor from vented or leaked batteries are inhalation, move to fresh air and get medical attention.

Ingestion: Get immediately medical attention, do not induce vomiting or give a liquid to unconscious person.

5. Fire Fighting Measures

Hazard Characteristic: Not available

Hazards Expose to Combustion Products: In case of fire, carbon dioxide, carbon monoxide and other toxic organic substances will be generated.

Do not inhale fumes and smoke.

Extinguishing Media: In case of fire, you can use any class of fire extinguisher. Special Fire Fighting Procedures: Fire fighters should wear self-contained breathing apparatus.

6. Accidental Release Measures

Precautions: Avoid direct contact with the leaking or ruptured cells. Avoid short circuit.

Methods for Clean Up: Care for well-ventilated conditions. Recycle or dispose of the materials in an appropriate way.

7. Handling and Storage

Precaution: Handing and transfer the products carefully, make sure the packing always in good condition. Damaged packing may cause cells contact together, in this case cells may short circuit or improperly connected, it cause cells venting, leaking or exploding.

Storage: Store in a dry, cool and well-ventilated area.



Head office :1728-1 OMAEDA FUKAYA-SHI,SAITAMA-KEN, 369-1295 JAPAN Battery Dept :3-12 SHIOHAMA, ICHIKAWA-SHI,CHIBA-KEN, 272-0127 JAPAN

8. Exposure Control/Personal Protection

Exposition/Technical Measures: Atmospheric vapor concentrations must be minimized by adequate ventilation.

Protection of Hands, Eyes, and Skin: No required under normal use conditions. When handling leaking cells, use gloves and wear safety glasses to protect hands, eyes and skin.

General Safety and Hygiene Measures: Use only as directed.

9. Physical and Chemical Properties

Physical State and Appearance: Cylindrical Odor: Odorless pH: N/A

Melting Point (°C): N/A Specific Gravity (H₂O=1): N/A Boiling Point (°C): N/A Vapor Density (Air=1): N/A

Vapor Pressure (kPa): N/A Heat of Combustion (kJ/mol): N/A

Critical Temperature (°C): N/A Critical Pressure (MPa): N/A

Partition Coefficient: N/A Flash Point (°C): N/A

Ignition Temperature (°C): N/A Explosion Limit % (V/V): N/A Solubility in Water: N/A Solubility in Other Solvents: N/A

10. Stability and Reactivity

Stability: Stable

Incompatibility: None

Condition to Avoid: Avoid shorting, mechanical & thermal abuse

Hazardous Polymerization: Will not occur

Hazardous Decomposition: None

11. Toxicological Information

Note: Since the materials in this cell are sealed in the can, the potential for exposure to the components of the cell is negligible, when the cell is used as directed. However technical or electrical abuse of the battery may result in the release of cell contents.

Toxicity to Animals: Not applicable

Chronic Effects on Human: Not applicable



Head office :1728-1 OMAEDA FUKAYA-SHI,SAITAMA-KEN, 369-1295 JAPAN Battery Dept :3-12 SHIOHAMA, ICHIKAWA-SHI,CHIBA-KEN, 272-0127 JAPAN

12. Ecological Information

This product has not been tested for environmental effects.

13. Disposal Consideration

Dispose in accordance with Federal, States and local regulations

14. Transport Information

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for Mitsubishi Electric Alkaline Button Cells has been designed to be compliant with these regulatory concerns.

Alkaline Button Cells (sometimes referred to as "Dry cell" batteries) are not listed as dangerous goods under the IATA Dangerous Goods Regulation 64th2023, ICAO Technical Instructions and the U.S. hazardous materials regulations (49 CFR). These batteries are not subject to the dangerous goods regulations provided they meet the requirements contained in the following special provisions.

Regulatory Body	Regulation	
ADR	Not regulate	
IMDG	Not regulate	
UN	Not regulate	
US DOT	Not regulate	
IATA	SP A123	
ICAO	Not regulate	

All Mitsubishi Electric Alkaline Button Cells are packed in such a way to prevent short circuits or the generation dangerous quantities of heat and meet the special provisions listed above. In addition, the IATA Dangerous Goods Regulations and ICAO Technical Instructions require the words "not restricted" and the Special Provision number A123 be provided on the air waybill, when an air waybill is issued.



Head office :1728-1 OMAEDA FUKAYA-SHI,SAITAMA-KEN, 369-1295 JAPAN Battery Dept :3-12 SHIOHAMA, ICHIKAWA-SHI,CHIBA-KEN, 272-0127 JAPAN

15. Regulatory Information

Special requirement be according to the local regulators.

16. Other information

Do not heat or dispose of in fire. Do not recharge or disassemble the battery.

Notice to reader:

The information contained in this SDS was obtained from current and reliable sources, however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of Mitsubishi Electric Home Appliance Co.,Ltd. Mitsubishi Electric Home Appliance Co.,Ltd will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.